

SPEC SHEET

Classroom Serv™ Ultra Pro



Specifications

Classroom Serv[™] Ultra Pro is constructed of 1-1/4" round stainless steel tubing and one serving counter with hygiene guard. The bottom shelf is 27-1/4" x 24", and the serving counter is 23-1/2" x 39-3/16". The serving counter is supported by 1-1/4" round stainless steel tubing. Includes a insulated food holding cabinet.

For transporting the hygiene guard folds down onto the serving counter and the serving counter folds up into the cart, as the serving counter leg folds under the serving counter.

The hygiene guard is made of 3/8" acrylic with a pass thru. The pass thru is 10" wide x 6" high.

The bottom is fully enclosed with Heavy Duty, Hi-Modulus Rubber Casters, 7" x 2", 2 front swivel with brake, 2 rigid in back.

ITEM	MODEL	WIDTH	DEPTH	HEIGHT
C1241	CSERVUP	32.18"	38.5"	74.75"

Options

☐ Additional	Serving	g Counte:	r for	Opposite	e Side
☐ Spirit Viny	l Banne	r			

PROJECT:	
	rd Features
□ Bottom	Fixed Shelf
□ Serving	
	e Guard - Acrylic
	s Steel Finish
	Outy, Hi-Modulus Rubber Casters
	d food holding cabinet choose one
•	ompartment
\square PCULP	Passive
	Electric Hot, 110v
	Electric Cold, 110v
	2 Electric Hot, 220v
□ PCULC:	2 Electric Cold, 220v
Dual Cor	npartment
□ PCUPP	Top Passive, Bottom Passive
□ PCUHH	I Electric, Top Hot, Bottom Hot, 110v
□ PCUHH	12 Electric, Top Hot, Bottom Hot, 220v
□ PCUCC	Electric, Top Cold, Bottom Cold, 110v
	2 Electric, Top Cold, Bottom Cold, 220v
	Electric, Top Hot, Bottom Cold, 110v
	2 Electric, Top Hot, Bottom Cold, 220v
	Electric, Top Cold, Bottom Hot, 110v
	2 Electric, Top Cold, Bottom Hot, 220v
	Electric, Top Hot, Bottom Passive, 110
□ PCUHP	2 Electric, Top Hot, Bottom Passive, 22

☐ PCUPC Electric, Top Passive, Bottom Cold, 110v

☐ PCUPC2 Electric, Top Passive, Bottom Cold, 220v



Trademark Applied

Rev 01/2021



Classroom Serv[™] Ultra Pro

